MURR ELEKTRONIK
stay connected

## PROFIBUS-PLUG-MALE (SUB-D) 90°

Screw terminals up to 12Mbits/s

Bus connection plug 90°
SUB-D9 (male), screw terminals
PROFIBUS

## Link to Product

### Illustration




Product may differ from Image

| Commercial data | |
|---|---|
| ECLASS-6.0 | 27279221 |
| ECLASS-7.0 | 27440104 |
| ECLASS-8.0 | 27440104 |
| ECLASS-9.0 | 27440102 |
| ECLASS-10.1 | 27242692 |
| ECLASS-11.1 | 27242692 |
| ECLASS-12.0 | 27242692 |
| ETIM-5.0 | EC002584 |
| customs tariff number | 85366990 |
| GTIN | 4048879049818 |
| Packaging unit | 1 |
| **Electrical data** | |
| Terminating resistor | connectable, integrated |
| **Electrical data \| Supply** | |
| Operating voltage DC min. | 4,75 V |
| Operating voltage DC max. | 5,25 V |
| Current consumption max. | 12,5 mA |
| **Industrial communication** | |
| Data transmission rate max. | 12 MBit/s |
| **Device protection \| Electrical** | |
| Degree of protection (EN IEC 60529) | IP20 |
| **Mechanical data \| Mounting data** | |
| Height | 64 mm |
| Width | 40 mm |
| Depth | 17 mm |

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-03-29

| Environmental characteristics \| Climatic | |
|---|---|
| Operating temperature min. | 0 °C |
| Operating temperature max. | 60 °C |
| Storage temperature min. | -25 °C |
| Storage temperature max. | 80 °C |

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-03-29