

## CAN-PLUG-MALE (SUB-D) 90°

Screw terminals up to 1Mbits/s

Bus connection plug 90°

SUB-D9 (female), screw terminals

max. 1 Mbit/s with switchable terminal resistors

CANopen

Plastic housings with good resistance against chemicals and oils.

The resistance to aggressive media should be individually tested for your application. Further details on request.

### [Link to Product](#)

#### Illustration



Product may differ from Image

#### Commercial data

ECLASS-6.0	27279221
ECLASS-7.0	27440104
ECLASS-8.0	27440104
ECLASS-9.0	27440102
ECLASS-10.1	27242692
ECLASS-11.1	27242692
ECLASS-12.0	27242692
ETIM-5.0	EC002584
customs tariff number	85366990
GTIN	4048879049825
Packaging unit	1

#### Electrical data

Terminating resistor	connectable, integrated
----------------------	-------------------------

#### Industrial communication

Data transmission rate max.	1 MBit/s
-----------------------------	----------

#### Installation

Connection cross section max.	1 mm <sup>2</sup>
-------------------------------	-------------------

#### Device protection | Electrical

Degree of protection (EN IEC 60529)	IP20
-------------------------------------	------

#### Mechanical data | Mounting data

Height	65 mm
--------	-------

Width	48 mm
-------	-------

Depth	16 mm
-------	-------

#### Environmental characteristics | Climatic

Operating temperature min.	0 °C
----------------------------	------

Operating temperature max.	60 °C
----------------------------	-------

Storage temperature min.	-25 °C
--------------------------	--------

Storage temperature max.	80 °C
--------------------------	-------

#### Important installation notes

Note on strain relief	Protect the connectors by suitable measures from mechanical loads, e.g. by the usage of cable ties.
-----------------------	---

Note on bending radius	<b>Attention:</b> Observe the permissible bending radii when laying cables, as the IP protection class can be endangered by excessive bending forces.
------------------------	---

#### Connection type 2

Family construction form	D-Sub
--------------------------	-------

Gender	female
--------	--------

No. of poles	9
--------------	---

PIN 2	CAN_L
-------	-------

PIN 3	CAN_GND
-------	---------

PIN 5	CAN_SHLD
-------	----------

PIN 6	0 V
-------	-----

PIN 7	CAN_H
-------	-------

PIN 9	CAN V +
-------	---------

Connection	Screw terminals SK
------------	--------------------

Family construction form	terminal
--------------------------	----------

Gender	female
--------	--------

No. of poles	6
--------------	---