

MKS - D 10/1300 - 1 DIODE MODULES


Mounting rail / screw-type terminal


Universal diode 1 300 V, 1 A 10 diodes separation contact via pluggable jumpers Diode modules are suitable for the suppression of inductive loads (valve, contactor, etc.)

Link to Product

Illustration







Product may differ from Image





27371010	
27371010	
27371010	
27371010	
27371010	
27371010	
	27371010 27371010 27371010 27371010

The information in this Product-PDF has been compiled with the utmost care.

Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-05-03



ECLASS-11.1	27371010
ECLASS-12.0	27371010
ETIM-5.0	EC002780
customs tariff number	85411000
GTIN	4048879041874
Packaging unit	1
Electrical data Supply	
Operating voltage AC max.	48 V
Operating voltage DC max.	48 V
Mechanical data Mounting data	
Mounting method	geschnappt
Suitable for mounting type	Mounting rail TH35, G32, (EN 60715)
Height	86 mm
Width	45 mm
Depth	62 mm
Environmental characteristics Climatic	
Operating temperature min.	-20 °C
Operating temperature max.	60 °C
Connection type 1	
Connection	Screw terminals SK
Family construction form	terminal
Gender	female
No. of poles	20