

M8 male recept. A-cod. front

PP-wires 4x0.25 0.2m

Flange male  
M8, 4-pole  
Front mounting  
with multi-strand wire

Link to Product

Illustration



Product may differ from Image



|                          |                   |
|--------------------------|-------------------|
| Cable length             | 0,2 m             |
| Side 1                   |                   |
| Tightening torque        | 0,4 Nm            |
| Mounting method          | inserted, screwed |
| Family construction form | M8                |

|   |   |
|---|---|
| Thread  | M8 x 1  |
| Material  | Brass   |
| Degree of protection (EN IEC 60529)             | IP67  |
| <b>Commercial data</b>                          |   |
| ECLASS-6.0                                      | 27279220  |
| ECLASS-6.1                                      | 27279220  |
| ECLASS-7.0                                      | 27440103  |
| ECLASS-8.0                                      | 27440103  |
| ECLASS-9.0                                      | 27440103  |
| ECLASS-10.1                                     | 27440103  |
| ECLASS-11.1                                     | 27440103  |
| ECLASS-12.0                                     | 27440103  |
| ETIM-5.0  | EC001855  |
| customs tariff number                           | 85444290  |
| GTIN  | 4048879434997   |
| Packaging unit                                  | 1   |
| <b>Electrical data   Supply</b>                 |   |
| Operating voltage AC max.                       | 50 V  |
| Operating voltage DC max.                       | 60 V  |
| Current operating per contact max.              | 4 A   |
| <b>Installation   Connection</b>                |   |
| Mounting set                                    | M8 x 1  |
| <b>Device protection   Electrical</b>           |   |
| Additional condition protection degree          | inserted, screwed   |
| Rated surge voltage                             | 0,8 kV  |
| <b>Mechanical data   Material data</b>          |   |
| Coating of fitting                              | nickel plated   |
| Material screw connection                       | Brass   |
| <b>Mechanical data   Mounting data</b>          |   |
| Mounting method                                 | Schraubgewinde  |
| Looking techniques                              | Schraubgewinde  |
| <b>Environmental characteristics   Climatic</b> |   |
| Operating temperature min.                      | -25 °C  |
| Operating temperature max.                      | 85 °C   |
| Additional condition temperature range          | depending on cable quality  |
| <b>Important installation notes</b>             |   |
| Note on strain relief                           | Protect the connectors by suitable measures from mechanical loads, e.g. by the usage of cable ties.   |
| Note on bending radius                          | <b>Attention:</b> Observe the permissible bending radii when laying cables, as the IP protection class can be endangered by excessive bending forces. |
| <b>Installation   Cable</b>                     |   |
| Cable identification                            | 969   |
| wire arrangement                                | brown, black, blue, white   |
| Material wire insulation                        | PP  |
| Amount wires                                    | 4   |
| Outer diameter insulation                       | 1,1 mm  |
| Outer diameter tolerance core insulation        | ± 5 %   |
| Conductor crosssection (wire)                   | 0,25 mm²  |
| Min. operating temperature (static)             | -40 °C  |
| Max. operating temperature (fixed)              | 90 °C   |
| Operating temperature min. (dynamic)            | -25 °C  |
| Operating temperature max. (dynamic)            | 90 °C   |

|                        |  |
|------------------------|--|
| Flame resistance       | IEC 60332-2-2   UL 1581 § 1090   UL 1581 § 1100 FT2  |
| chemical resistance    | Good, application-related testing                    |
| Gasoline resistance    | Good, application-related testing                    |
| Oil resistance         | Good, application-related testing   DIN EN 60811-404 |
| Bending radius (fixed) | 5 x Outer diameter                                   |