

Adapter M12 male/ female B-cod. / D-Sub 9-pol. 35°

Shielded, 12Mbit/s

PROFIBUS
Bus connection plug 35°
SUB-D9 (male); M12× 1 mm, B-coded
Programming device

Link to Product

Illustration



Product may differ from Image

| Commercial data | |
|-------------------------------------|-------------------------|
| ECLASS-6.0 | 27061801 |
| ECLASS-7.0 | 27061801 |
| ECLASS-8.0 | 27061801 |
| ECLASS-9.0 | 27061801 |
| ECLASS-10.1 | 27242692 |
| ECLASS-11.1 | 27242692 |
| ECLASS-12.0 | 27242692 |
| ETIM-5.0 | EC001855 |
| customs tariff number | 85366990 |
| GTIN | 4048879303620 |
| Packaging unit | 1 |
| Electrical data | |
| Terminating resistor | connectable, integrated |
| Electrical data Supply | |
| Operating voltage DC min. | 4,75 V |
| Operating voltage DC max. | 5,25 V |
| Current consumption max. | 12,5 mA |
| Industrial communication | |
| Data transmission rate max. | 12 MBit/s |
| Installation Connection | |
| Family construction form | M12 |
| Device protection Electrical | |
| Degree of protection (EN IEC 60529) | IP30 |
| Mechanical data Mounting data | |

| | |
|--|---|
| Height | 68 mm |
| Width | 42 mm |
| Depth | 17 mm |
| Environmental characteristics Climatic | |
| Operating temperature min. | -20 °C |
| Operating temperature max. | 70 °C |
| Important installation notes | |
| Note on strain relief | Protect the connectors by suitable measures from mechanical loads, e.g. by the usage of cable ties. |
| Note on bending radius | Attention: Observe the permissible bending radii when laying cables, as the IP protection class can be endangered by excessive bending forces. |