

MICO+ 4.4 electronic circuit protection, 4 CHANNELS


IN: 24 V DC OUT: 24 V / 1-2-3-4 A CL2


MICO+ 4.4 4 channels Current adjustment 1, 2, 3, 4 A

Link to Product

Illustration







Product may differ from Image











Commercial data		
ECLASS-6.0	27371802	
ECLASS-6.1	27371802	
ECLASS-7.0	27371802	
ECLASS-8.0	27371802	
ECLASS-9.0	27371802	
ECLASS-10.1	27371802	



stay connected

ECLASS-11.1	27371802
ECLASS-12.0	27371802
ETIM-5.0	EC001440
customs tariff number	85363010
GTIN	4048879328920
Packaging unit	1
Electrical data Input	
Input voltage DC	24 V
Input voltage DC min.	18 V
Input voltage DC max.	30 V
ON input voltage control inputs min.	10 V
ON input voltage control inputs max.	30 V
ON pulse length control inputs high min.	20 ms
Total current bridge set max.	40 A
Electrical data Output	
Switch-on capacity per channel max.	20 mF
Switching current max.	20 mA
Installation	
Connection cross-section inputs max.	16 mm ²
Connection cross-section outputs max.	1.5 mm²
Connection cross-section control inputs /	
control outputs max.	2,5 mm²
Mechanical data Mounting data	
Mounting method	geschnappt
Suitable for mounting type	Mounting rail TH35, (EN 60715)
Height	90 mm
Width	70 mm
Depth	80 mm
Environmental characteristics Climatic	
Operating temperature min.	0 °C
Operating temperature max.	55 °C
Storage temperature min.	-40 °C
Storage temperature max.	80 °C
Connection type 10	
Family construction form	Bridging Contact
Gender	female
Color contact carrier	black
No. of poles	1
PIN 1	24 V DC
Family construction form	Bridging Contact
Gender	female
Color contact carrier	black
No. of poles	1
PIN 1	0 V
Family construction form	Bridging Contact
Gender	female
Color contact carrier	black
No. of poles	2
PIN 1	On
PIN 2	Off
Connection	Spring clamp terminals FK
Family construction form	terminal
Lanniy Gunanagiluliyi iyilli	torrima

The information in this Product-PDF has been compiled with the utmost care. Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-05-03



stay connected

	female
Color contact carrier	green
No. of poles	1
PIN 1	0 V
Connection	Spring clamp terminals FK
Family construction form	terminal
Gender	female
Color contact carrier	green
No. of poles	1
PIN 1	24 V DC
Connection	Spring clamp terminals FK
Family construction form	terminal
Gender	female
Color contact carrier	green
No. of poles	2
PIN 1	Out 1
PIN 2	Out 1
Connection	Spring clamp terminals FK
Family construction form	terminal
Gender	female
Color contact carrier	green
No. of poles	2
PIN 1	Out 2
PIN 2	Out 2
Connection	Spring clamp terminals FK
Family construction form	terminal
Gender	female
Color contact carrier	green
No. of poles	2
PIN 1	Out 3
PIN 2	Out 3
Connection	Spring clamp terminals FK
Family construction form	terminal
Gender	female
Color contact carrier	green
No. of poles	2
er er	
PIN 1	Out 4
	Out 4 Out 4
PIN 1 PIN 2 Connection	
PIN 1 PIN 2	Out 4
PIN 1 PIN 2 Connection Family construction form Gender	Out 4 Spring clamp terminals FK
PIN 1 PIN 2 Connection Family construction form	Out 4 Spring clamp terminals FK terminal
PIN 1 PIN 2 Connection Family construction form Gender	Out 4 Spring clamp terminals FK terminal female
PIN 1 PIN 2 Connection Family construction form Gender Color contact carrier No. of poles PIN 1	Out 4 Spring clamp terminals FK terminal female green
PIN 1 PIN 2 Connection Family construction form Gender Color contact carrier No. of poles PIN 1 PIN 2	Out 4 Spring clamp terminals FK terminal female green 4
PIN 1 PIN 2 Connection Family construction form Gender Color contact carrier No. of poles PIN 1	Out 4 Spring clamp terminals FK terminal female green 4 On