



RMMDU 11/24 OUTPUT RELAY

IN: 24 VDC - OUT: 250 VAC/DC / 8 A

1 relay; 1 NO/NC contact
8 A
24 V DC
with minus plug link

[Link to Product](#)**Illustration**

Product may differ from Image

General data

Mech./ elect. life	20 000 000 switching cycles/load dependent
Test isolation voltage	5 kV; safe separation (IEC 61140/EN 61140)
Mounting method	DIN-rail mountable TH35 or G32 (EN 60715)
Temperature range	-20...+50 °C
Dimensions HxWxD	82x12x68 mm

Output

Switching voltage	max. 250 V AC/DC
Switching current per output	max. 8 A
Min. load current	100 mA
Power rating (voltage dependent)	max. 2000 VA/240 W
Switching frequency	max. 10 Hz
Contact material	Ag Ni
Energize/release/contact bounce time	10/15/2 ms

Input

The information in this brochure has been compiled with the utmost care.

Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 10/21

Connection voltage - current	24 V DC (21.6...26.4 V DC) - 15 mA
Plug link (supplied)	Art-No. 90960
LED display	LED (red)
Utilization category	
AC-1	8 A (24/110/230 V AC)
AC-15	3 A (24/110/230 V AC)
DC-13	2.5 A (24 V DC); 0.4 A (110 V DC); 0.3 A (230 V DC)
Commercial data	
country of origin	CZ
customs tariff number	85364900
EAN	4048879027779
eClass	27371001
Packaging unit	1