



**RM-21/24V AC/DC KL.BZ.N.EN OUTPUT RELAY**

IN: 24 VAC/DC - OUT: 250 VAC/DC / 5 A

2 relays; each 1 NO/NC contact  
 8 A  
 24 V DC  
 Screw terminals

[Link to Product](#)**Illustration**

Product may differ from Image

**General data**

Mech./ elect. life	20 000 000 switching cycles/load dependent
Test isolation voltage	4.0 kV
Mounting method	DIN-rail mountable TH35 or G32 (EN 60715)
Temperature range	-20...+50 °C
Dimensions HxWxD	75x22.5x102 mm

**Output**

Switching voltage	max. 250 V AC/DC
Switching current per output	max. 8 A
Min. load current	100 mA
Power rating (voltage dependent)	max. 1250 VA/240 W
Switching frequency	max. 0.1 Hz (with load)
Contact material	Ag Sn O <sub>2</sub>
Energize/release/contact bounce time	10/10/2 ms

Input	
Connection voltage - current	24 V AC/DC (19.2...30 V AC/DC) - 10 mA
LED display	LED (red)
Utilization category	
AC-1	8 A (24/110/230 V AC)
AC-15	3 A (24/110/230 V AC)
DC-13	1.5 A (24 V DC); 0.3 A (110 V DC); 0.15 A (230 V DC)
Commercial data	
country of origin	CZ
customs tariff number	85364900
EAN	4048879027595
eClass	27371001
Packaging unit	1