MURR ELEKTRONIK
stay connected

## SV-SUB D 25ST.-KL FOR SIGNAL TRANSFER


125 VAC/DC / 2 A


Male connector
25-pole
Screw terminals

**Link to Product**

### Illustration






Product may differ from Image

### Commercial data

| | |
|---|---|
| ECLASS-6.0 | 27143424 |
| ECLASS-6.1 | 27260708 |
| ECLASS-7.0 | 27141152 |
| ECLASS-8.0 | 27141152 |
| ECLASS-9.0 | 27141152 |
| ECLASS-10.1 | 27141152 |

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-03-19

MURR ELEKTRONIK
stay connected

| | |
|---|---|
| ECLASS-11.1 | 27141152 |
| ECLASS-12.0 | 27141152 |
| ETIM-5.0 | EC001283 |
| customs tariff number | 85366990 |
| GTIN | 4048879026529 |
| Packaging unit | 1 |
| **Electrical data \| Supply** | |
| Operating voltage AC | 125 V |
| Operating voltage DC | 150 V |
| Operating current max. | 2 A |
| **Device protection \| Electrical** | |
| Overvoltage category (EN 60664-1) | II |
| **Mechanical data \| Mounting data** | |
| Mounting method | geschnappt |
| Suitable for mounting type | mounting rail, (EN 60715) |
| Height | 63 mm |
| Width | 95 mm |
| Depth | 48 mm |
| Looking techniques | Standard UNC 4-40 screw thread bolt (EN 60807) |
| **Environmental characteristics \| Climatic** | |
| Operating temperature min. | -20 °C |
| Operating temperature max. | 70 °C |

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-03-19