



LUG S 8 FOR SIGNAL TRANSFER

250V / 8 A

8-pole  
Screw plug-in terminals

[Link to Product](#)

Illustration



Product may differ from Image

| Commercial data       |               |
|-----------------------|---------------|
| ECLASS-6.0            | 27143424      |
| ECLASS-6.1            | 27260708      |
| ECLASS-7.0            | 27141152      |
| ECLASS-8.0            | 27141152      |
| ECLASS-9.0            | 27141152      |
| ECLASS-10.1           | 27141152      |
| ECLASS-11.1           | 27141152      |
| ECLASS-12.0           | 27141152      |
| ETIM-5.0              | EC001283      |
| customs tariff number | 85369010      |
| GTIN                  | 4048879026291 |
| Packaging unit        | 1             |

| Electrical data   Supply                 |                           |
|--|---------------------------|
| Operating voltage AC                     | 250 V                     |
| Operating current max.                   | 8 A                       |
| Installation                             |                           |
| Connection cross-section solid max.      | 4 mm <sup>2</sup>         |
| Installation   Connection                |                           |
| Connection                               | Screw terminals SK        |
| Mechanical data   Mounting data          |                           |
| Mounting method                          | geschnappt                |
| Suitable for mounting type               | mounting rail, (EN 60715) |
| Height                                   | 75 mm                     |
| Width                                    | 45 mm                     |
| Depth                                    | 66 mm                     |
| Environmental characteristics   Climatic |                           |
| Operating temperature min.               | -20 °C                    |
| Operating temperature max.               | 60 °C                     |