

IMPACT67 COMPACT MODULE, PLASTIC

CANopen, 16 dig Out


Digital outputs
DO16 - 0.5 A
CAN 1 Mbit/s; M12, A-coded
7/8", 5-pole, 2× max. 9 A
M12, 5-pole, A-coded
Connection cables are in the online shop under "Connection Technology".
Housing fully potted.
mounting compatible with I/O modules of the MVK series

Link to Product

Illustration



Product may differ from Image



Commercial data

ECLASS-6.0	27242604
ECLASS-6.1	27242604
ECLASS-7.0	27242604
ECLASS-8.0	27242604
ECLASS-9.0	27242604
ECLASS-10.1	27242604
ECLASS-11.1	27242604
ECLASS-12.0	27242604
ETIM-5.0	EC001604
customs tariff number	85389099
GTIN	4048879052009
Packaging unit	1

Electrical data | Supply

Total current UA max.	9 A
Total current US max.	9 A

Electrical data | Output

Overload resistant	yes
--------------------	-----

Short-circuit protected	yes
-------------------------	-----

Output current per pin max.	0,5 A
-----------------------------	-------

Industrial communication | Bus data

Address range min.	1
--------------------	---

Address range max.	99
--------------------	----

Industrial communication | CANopen

CANopen addressing	Rotary switch
--------------------	---------------

Diagnostics

Diagnostic	No voltage, Under voltage
------------	---------------------------

Diagnostic via BUS	per module and channel
--------------------	------------------------

Diagnostic via LED	per module and channel
--------------------	------------------------

LED display	Ethernet connection/data traffic
-------------	----------------------------------

Device protection | Electrical

Degree of protection (EN IEC 60529)	IP67
-------------------------------------	------

Mechanical data | Mounting data

Suitable for mounting type	2-hole screw mounting
----------------------------	-----------------------

Height	39 mm
--------	-------

Width	63 mm
-------	-------

Depth	225 mm
-------	--------

Environmental characteristics | Climatic

Operating temperature min.	-25 °C
----------------------------	--------

Operating temperature max.	70 °C
----------------------------	-------

Storage temperature min.	-25 °C
--------------------------	--------

Storage temperature max.	70 °C
--------------------------	-------

Connection type 5

Connection type 1	0-7
-------------------	-----

Connection type 2	Bus In
-------------------	--------

Connection type 3	Bus Out
-------------------	---------

Connection type 4	Power In
-------------------	----------

Connection type 5	Power Out
-------------------	-----------

Family construction form	M12
--------------------------	-----

Gender	female
--------	--------

Color contact carrier	gray
-----------------------	------

Coding	A
--------	---

No. of poles	5
--------------	---

PIN 1	n.c.
-------	------

PIN 2	DO 10-17
-------	----------

PIN 3	0 V
-------	-----

PIN 4	DO 00-07
-------	----------

PIN 5	PE
-------	----

Family construction form	M12
--------------------------	-----

Gender	male
--------	------

Color contact carrier	black
-----------------------	-------

Coding	A
--------	---

No. of poles	5
--------------	---

PIN 1	PE
-------	----

PIN 2	n.c.
-------	------

PIN 3	CAN_PE
-------	--------

PIN 4	CAN_HIGH
-------	----------

PIN 5	CAN_LOW
-------	---------

Family construction form	M12
Gender	female
Color contact carrier	black
Coding	A
No. of poles	5
PIN 1	PE
PIN 2	n.c.
PIN 3	CAN_PE
PIN 4	CAN_HIGH
PIN 5	CAN_LOW
Family construction form	7/8"
Gender	male
Color contact carrier	black
No. of poles	5
PIN 1	0 V
PIN 2	0 V
PIN 3	PE
PIN 4	24 V DC (US)
PIN 5	24 V DC (UA)
Family construction form	7/8"
Gender	female
Color contact carrier	black
No. of poles	5
PIN 1	0 V
PIN 2	0 V
PIN 3	PE
PIN 4	24 V DC (US)
PIN 5	24 V DC (UA)