

CAN-PLUG-MALE (SUB-D) 90°

Screw terminals up to 1Mbits/s

Bus connection plug 90°

SUB-D9 (female), screw terminals

max. 1 Mbit/s with switchable terminal resistors

CANopen

Plastic housings with good resistance against chemicals and oils.

The resistance to aggressive media should be individually tested for your application. Further details on request.

[Link to Product](#)

Illustration



Product may differ from Image

Commercial data

ECLASS-6.0	27279221
ECLASS-7.0	27440104
ECLASS-8.0	27440104
ECLASS-9.0	27440102
ECLASS-10.1	27242692
ECLASS-11.1	27242692
ECLASS-12.0	27242692
ETIM-5.0	EC002584
customs tariff number	85366990
GTIN	4048879049825
Packaging unit	1

Electrical data

Terminating resistor	connectable, integrated
----------------------	-------------------------

Industrial communication

Data transmission rate max.	1 MBit/s
-----------------------------	----------

Installation

Connection cross section max.	1 mm ²
-------------------------------	-------------------

Device protection | Electrical

Degree of protection (EN IEC 60529)	IP20
-------------------------------------	------

Mechanical data | Mounting data

Height	65 mm
--------	-------

Width	48 mm
-------	-------

Depth	16 mm
-------	-------

Environmental characteristics | Climatic

Operating temperature min.	0 °C
----------------------------	------

Operating temperature max.	60 °C
----------------------------	-------

Storage temperature min.	-25 °C
--------------------------	--------

Storage temperature max.	80 °C
--------------------------	-------

Connection type 2

Family construction form	D-Sub
--------------------------	-------

Gender	female
--------	--------

No. of poles	9
--------------	---

PIN 2	CAN_L
-------	-------

PIN 3	CAN_GND
-------	---------

PIN 5	CAN_SHLD
-------	----------

PIN 6	0 V
-------	-----

PIN 7	CAN_H
-------	-------

PIN 9	CAN V +
-------	---------

Connection	Screw terminals SK
------------	--------------------

Family construction form	terminal
--------------------------	----------

Gender	female
--------	--------

No. of poles	6
--------------	---