

ASSEMBLY MODULE MP 6


Mounting rail / screw-type terminal


6 pairs of solder pins screw terminals connected to solder pin pairs

Link to Product

Illustration







Product may differ from Image





Commercial data		
ECLASS-6.0	27260710	
ECLASS-6.1	27141149	
ECLASS-7.0	27141149	
ECLASS-8.0	27141149	
ECLASS-9.0	27141149	
ECLASS-10.1	27141149	
ECLASS-11.1	27141149	
ECLASS-12.0	27141149	

The information in this Product-PDF has been compiled with the utmost care.

Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-04-26



stay connected

ETIM-5.0	EC000683	
customs tariff number	85369010	
GTIN	4048879042277	
Packaging unit	1	
Electrical data Supply		
Operating voltage AC	50 V	
Operating voltage DC	50 V	
Operating current max.	5 A	
Installation		
Connection cross section max.	4 mm ²	
Installation Connection		
Connection	Screw terminals SK	
Connection information	Lötstützpunktpaare (Raster 5 mm)	
Device protection Media		
Flame resistance	flame retardant	
Mechanical data Material data		
Housing properties	open design	
Material housing	Plastic	
Mechanical data Mounting data		
Distance of solder pins	24 mm	
Mounting method	screwed, geschnappt	
Suitable for mounting type	Mounting rail TH35, G32, (EN 60715)	
Height	63 mm	
Width	45 mm	
Depth	36 mm	
Environmental characteristics Climatic	c	
Operating temperature min.	-20 °C	
Operating temperature max.	60 °C	