MURR ELEKTRONIK
stay connected

LED-INDICATOR OPAC / RED


LED-230VAC IP65

(red)
230 V AC
The modules are suitable for wall thickness of 1.5...5.0 mm.

Link to Product

Illustration





Product may differ from Image

Commercial data	
ECLASS-6.0	27261590
ECLASS-6.1	27261501
ECLASS-7.0	27261501
ECLASS-8.0	27261501
ECLASS-9.0	27261501
ECLASS-10.1	27261501
ECLASS-11.1	27261501
ECLASS-12.0	27261501
ETIM-5.0	EC000272
customs tariff number	85318070
GTIN	4048879041317
Packaging unit	10
Electrical data | Supply	
Operating voltage AC	230 V
Operating voltage AC min.	207 V
Operating voltage AC max.	253 V
Current consumption min.	8 mA
Current consumption max.	12 mA
Installation | Connection	
Connection information	Faston 2.8×0.8 mm
Device protection | Electrical	
Degree of protection (EN IEC 60529)	IP65
Device protection | Media	
Flame resistance	flame retardant
Mechanical data	

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-03-28

Diameter LED	5 mm
Mechanical data | Material data	
Material housing	Plastic
Mechanical data | Mounting data	
Diameter front panel drilling	9 mm
Environmental characteristics | Climatic	
Operating temperature min.	-20 °C
Operating temperature max.	50 °C

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-03-28