

LUG S 8 FOR SIGNAL TRANSFER


250V / 8 A


8-pole Screw plug-in terminals

Link to Product

Illustration







Product may differ from Image

Commercial data		
ECLASS-6.0	27143424	
ECLASS-6.1	27260708	
ECLASS-7.0	27141152	
ECLASS-8.0	27141152	
ECLASS-9.0	27141152	
ECLASS-10.1	27141152	
ECLASS-11.1	27141152	
ECLASS-12.0	27141152	
ETIM-5.0	EC001283	
customs tariff number	85369010	
GTIN	4048879026291	
Packaging unit	1	

The information in this Product-PDF has been compiled with the utmost care. Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-05-04



stay connected

Electrical data Supply	
Operating voltage AC	250 V
Operating current max.	8 A
Installation	
Connection cross-section solid max.	4 mm ²
Installation Connection	
Connection	Screw terminals SK
Mechanical data Mounting data	
Mounting method	geschnappt
Suitable for mounting type	mounting rail, (EN 60715)
Height	75 mm
Width	45 mm
Depth	66 mm
Environmental characteristics Climatic	
Operating temperature min.	-20 °C
Operating temperature max.	60 °C