MURR ELEKTRONIK
stay connected

## LED-INDICATOR OPAC / RED

LED-110V IP65

(red)
110 V AC/DC
The modules are suitable for wall thickness of 1.5...5.0 mm.

Link to Product

### Illustration




Product may differ from Image

| Commercial data | |
|---|---|
| ECLASS-6.0 | 27261590 |
| ECLASS-6.1 | 27261501 |
| ECLASS-7.0 | 27261501 |
| ECLASS-8.0 | 27261501 |
| ECLASS-9.0 | 27261501 |
| ECLASS-10.1 | 27261501 |
| ECLASS-11.1 | 27261501 |
| ECLASS-12.0 | 27261501 |
| ETIM-5.0 | EC000272 |
| customs tariff number | 85318070 |
| GTIN | 4048879041324 |
| Packaging unit | 10 |
| **Electrical data \| Supply** | |
| Operating voltage AC | 110 V |
| Operating voltage AC min. | 95 V |
| Operating voltage AC max. | 121 V |
| Operating voltage DC | 110 V |
| Operating voltage DC min. | 95 V |
| Operating voltage DC max. | 121 V |
| Current consumption min. | 8 mA |
| Current consumption max. | 12 mA |
| **Installation \| Connection** | |
| Connection information | Faston 2.8×0.8 mm |
| **Device protection \| Electrical** | |
| Degree of protection (EN IEC 60529) | IP65 |

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-04-30

| | |
|---|---|
| **Device protection \| Media** | |
| Flame resistance | flame retardant |
| **Mechanical data** | |
| Diameter LED | 5 mm |
| **Mechanical data \| Material data** | |
| Material housing | Plastic |
| **Mechanical data \| Mounting data** | |
| Diameter front panel drilling | 9 mm |
| **Environmental characteristics \| Climatic** | |
| Operating temperature min. | -20 °C |
| Operating temperature max. | 50 °C |

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-04-30