

MODLINK MSDD DATA INSERT

4×USB-A female/female

USB; USB; USB; USB (form A)  
4× USB (female/female) form A

Link to Product

Illustration



Product may differ from Image



Commercial data

|                       |               |
|-----------------------|---------------|
| ECLASS-6.0            | 27189217      |
| ECLASS-6.1            | 27189217      |
| ECLASS-7.0            | 27189217      |
| ECLASS-8.0            | 27189217      |
| ECLASS-9.0            | 27189217      |
| ECLASS-10.1           | 27182806      |
| ECLASS-11.1           | 27182806      |
| ECLASS-12.0           | 27182806      |
| ETIM-5.0              | EC002625      |
| customs tariff number | 85366990      |
| GTIN                  | 4048879037792 |
| Packaging unit        | 1             |

Mechanical data | Mounting data

|        |       |
|--------|-------|
| Height | 88 mm |
| Width  | 51 mm |
| Depth  | 45 mm |

Environmental characteristics | Climatic

|                          |        |
|--------------------------|--------|
| Storage temperature min. | -20 °C |
| Storage temperature max. | 60 °C  |

USB

|                      |      |
|----------------------|------|
| Operating voltage AC | 48 V |
|----------------------|------|

|                                  |                   |
|----------------------------------|-------------------|
| Operating voltage DC             | 48 V              |
| Operating voltage DC (UL-listed) | 42,4 V            |
| Operating current max.           | 500 mA            |
| USB specification                | 2.0               |
| Data transmission rate max.      | 480 MBit/s        |
| Looking techniques               | Snap-in connector |