

MODLINK MSDD DATA INSERT

1×SUB-D9 female/female Profi bus interface

- SUB-D9
- 1× SUB-D9 (blind plug)
- 1× SUB-D9 (female) PROFIBUS

Link to Product

Illustration



Product may differ from Image



| Commercial data                          |               |
|------------------------------------------|---------------|
| ECLASS-6.0                               | 27189217      |
| ECLASS-6.1                               | 27189217      |
| ECLASS-7.0                               | 27189217      |
| ECLASS-8.0                               | 27189217      |
| ECLASS-9.0                               | 27182806      |
| ECLASS-10.1                              | 27182806      |
| ECLASS-11.1                              | 27182806      |
| ECLASS-12.0                              | 27182806      |
| ETIM-5.0                                 | EC002625      |
| customs tariff number                    | 85366990      |
| GTIN                                     | 4048879301947 |
| Packaging unit                           | 1             |
| Mechanical data   Mounting data          |               |
| Height                                   | 88 mm         |
| Width                                    | 51 mm         |
| Depth                                    | 40 mm         |
| Environmental characteristics   Climatic |               |
| Storage temperature min.                 | 5 °C          |
| Storage temperature max.                 | 40 °C         |
| SUB-D9                                   |               |
| Operating voltage AC                     | 48 V          |

|                                       |                                                |
|---------------------------------------|------------------------------------------------|
| Operating voltage DC                  | 48 V                                           |
| Operating voltage AC max. (UL-listed) | 30 V                                           |
| Operating voltage DC max. (UL-listed) | 42,4 V                                         |
| Operating current                     | 3 A                                            |
| Current operating max. (UL)           | 175 mA                                         |
| Family construction form              | SUB-D9                                         |
| Family type Back side                 | SUB-D9                                         |
| Gender                                | female                                         |
| Gender Rear                           | female                                         |
| Looking techniques                    | Standard UNC 4-40 screw thread bolt (EN 60807) |
| No. of poles                          | 9                                              |