

COMLIGHT56 LED AMBER STATUS LIGHT

With 4 pole M12 bottom exit

Compact status light  
Flange M12 male, 4-pole  
yellow

Link to Product

Illustration



Product may differ from Image



| Commercial data                        |                  |
|----------------------------------------|------------------|
| ECLASS-6.0                             | 27371220         |
| ECLASS-6.1                             | 27110390         |
| ECLASS-7.0                             | 27110390         |
| ECLASS-8.0                             | 27110390         |
| ECLASS-9.0                             | 27110350         |
| ECLASS-10.1                            | 27110350         |
| ECLASS-11.1                            | 27110350         |
| ECLASS-12.0                            | 27110350         |
| ETIM-5.0                               | EC000232         |
| customs tariff number                  | 85319000         |
| GTIN                                   | 4048879855716    |
| Packaging unit                         | 1                |
| Electrical data   Supply               |                  |
| Operating voltage DC                   | 24 V             |
| Current consumption max.               | 26 mA            |
| Industrial communication   HMI         |                  |
| Luminous intensity                     | 1340 mcd         |
| Device protection   Electrical         |                  |
| Degree of protection (EN IEC 60529)    | IP65             |
| Additional condition protection degree | inserted, locked |

**Mechanical data | Material data**

|                  |         |
|------------------|---------|
| Material housing | Plastic |
|------------------|---------|

**Mechanical data | Mounting data**

|        |         |
|--------|---------|
| Height | 78,8 mm |
| Width  | 56 mm   |
| Depth  | 56 mm   |

**Environmental characteristics | Climatic**

|                            |        |
|----------------------------|--------|
| Operating temperature min. | -30 °C |
| Operating temperature max. | 50 °C  |

**Connection type 1**

|                          |                  |
|--------------------------|------------------|
| Family construction form | M12              |
| Gender                   | male             |
| Coding                   | A                |
| No. of poles             | 4                |
| PIN 3                    | BU 0 V (24 V DC) |
| PIN 4                    | BK 24 V DC (0 V) |