

Modlight70 Pro connecting modul tube mounting

Input 24VDC

Basic for tube mounting  
Connection cables are in the online shop under "Connection Technology".

Link to Product

Illustration



Product may differ from Image



Commercial data

|                       |               |
|-----------------------|---------------|
| ECLASS-6.0            | 27371232      |
| ECLASS-6.1            | 27371232      |
| ECLASS-7.0            | 27371232      |
| ECLASS-8.0            | 27371232      |
| ECLASS-9.0            | 27371232      |
| ECLASS-10.1           | 27371232      |
| ECLASS-11.1           | 27371232      |
| ECLASS-12.0           | 27371232      |
| ETIM-5.0              | EC001152      |
| ETIM-6.0              | EC001152      |
| ETIM-7.0              | EC001152      |
| customs tariff number | 85319000      |
| GTIN                  | 4048879752480 |
| Packaging unit        | 1             |

Electrical data | Supply

|                           |        |
|---------------------------|--------|
| Operating voltage DC      | 24 V   |
| Operating voltage DC min. | 21,6 V |
| Operating voltage DC max. | 26,4 V |

Device protection | Electrical

|                                        |                  |
|----------------------------------------|------------------|
| Degree of protection (EN IEC 60529)    | IP65             |
| Additional condition protection degree | inserted, locked |

Mechanical data | Material data

|                                                 |                 |
|-------------------------------------------------|-----------------|
| Color housing                                   | black           |
| Material housing                                | Plastic         |
| <b>Mechanical data   Mounting data</b>          |                 |
| Height                                          | 99 mm           |
| Width                                           | 70 mm           |
| Depth                                           | 70 mm           |
| <b>Environmental characteristics   Climatic</b> |                 |
| Operating temperature min.                      | -30 °C          |
| Operating temperature max.                      | 60 °C           |
| <b>Connection type 1</b>                        |                 |
| Mounting method                                 | bayonet-locking |