

Signal tower Modlight70 Pro equipped with LED modules

green,amber,red,M12 plug downward

Basic + LED modules + M12 (down)  
green, yellow, red


Link to Product

Illustration



Product may differ from Image

Male



PIN 1: +  
PIN 2: LED (red)  
PIN 3: –  
PIN 4: LED (clear)  
PIN 5: LED (yellow)  
PIN 6: LED (blue)  
PIN 7: LED (green)  
PIN 8: Continious alarm



Commercial data

ECLASS-6.0	27371230
ECLASS-6.1	27371230
ECLASS-7.0	27371230
ECLASS-8.0	27371230
ECLASS-9.0	27371230
ECLASS-10.1	27371230
ECLASS-11.1	27371230
ECLASS-12.0	27371230
ETIM-5.0	EC001042
customs tariff number	85318070
GTIN	4048879759922
Packaging unit	1

Electrical data | Supply

Operating voltage DC	24 V
Operating voltage DC min.	21,6 V
Operating voltage DC max.	26,4 V
Current consumption max.	135 mA

Device protection | Electrical

Degree of protection (EN IEC 60529)	IP65
Additional condition protection degree	inserted, locked

Mechanical data | Material data

Color housing	black
---------------	-------

Mechanical data   Mounting data	
Height	293 mm
Width	70 mm
Depth	70 mm
Environmental characteristics   Climatic	
Operating temperature min.	-30 °C
Operating temperature max.	60 °C