

Signal tower Modlight70 Pro equipped with LED modules

green,amber,red,buzzer,M12 plug side

Basic, buzzer, flash + LED modules + M12 (side)  
green, yellow, red


Link to Product

Illustration



Product may differ from Image

Male



PIN 1: +  
PIN 2: LED (red)  
PIN 3: –  
PIN 4: LED (clear)  
PIN 5: LED (yellow)  
PIN 6: LED (blue)  
PIN 7: LED (green)  
PIN 8: Continious alarm



Commercial data	
ECLASS-6.0	27371230
ECLASS-6.1	27371230
ECLASS-7.0	27371230
ECLASS-8.0	27371230
ECLASS-9.0	27371230
ECLASS-10.1	27371230
ECLASS-11.1	27371230
ECLASS-12.0	27371230
ETIM-5.0	EC001042
customs tariff number	85318070
GTIN	4048879759953
Packaging unit	1
Electrical data   Supply	
Operating voltage DC	24 V
Operating voltage DC min.	21,6 V
Operating voltage DC max.	26,4 V
Current consumption max.	385 mA
Industrial communication   HMI	
Buzzer sound	fast beep, continuous beep, fast high-low, sweep tone
Reduced sound pressure at 1 m	80 dB
Sound pressure at 1 m	90 dB
HMI   Illumination properties	

Blink cycles 60 ±12 per minute

**Device protection | Electrical**

Degree of protection (EN IEC 60529) IP65  
Additional condition protection degree inserted, locked

**Mechanical data | Material data**

Color housing black  
Material housing Plastic

**Mechanical data | Mounting data**

Height 293 mm  
Width 70 mm  
Depth 70 mm

**Environmental characteristics | Climatic**

Operating temperature min. -30 °C  
Operating temperature max. 60 °C