

SVS VALVE PLUG FORM A 18MM FIELD-WIREABLE


110V/230V LED+RC PG9

Form A (18 mm)  
110/230 V AC/DC  
LED and RC  
PG9

Plastic housings with good resistance against chemicals and oils.  
The resistance to aggressive media should be individually tested for your application. Further details on request.

Link to Product

Illustration



Product may differ from Image

Side 1

Degree of protection (EN IEC 60529) IP65

Commercial data

ECLASS-6.0	27279221
ECLASS-7.0	27440104
ECLASS-8.0	27440104
ECLASS-9.0	27440102
ECLASS-10.1	27440105
ECLASS-11.1	27440105

ECLASS-12.0	27440105
ETIM-5.0	EC002062
customs tariff number	85366990
GTIN	4048879187572
Packaging unit	1

**Electrical data | Supply**

Operating voltage AC min.	110 V
Operating voltage AC max.	230 V
Operating voltage DC min.	110 V
Operating voltage DC max.	230 V
Current operating per contact max.	1 A

**Installation | Connection**

Tightening torque	0,4 Nm
Mounting set	M3

**Installation | Pin assignment**

No. of poles	2 + PE
--------------	--------

**Device protection | Electrical**

Additional condition protection degree	inserted, screwed
--	-------------------

**Environmental characteristics | Climatic**

Operating temperature min.	-20 °C
Operating temperature max.	60 °C

**Important installation notes**

Note on strain relief	Protect the connectors by suitable measures from mechanical loads, e.g. by the usage of cable ties.
Note on bending radius	<b>Attention:</b> Observe the permissible bending radii when laying cables, as the IP protection class can be endangered by excessive bending forces.