



Push Pull RJ45 male 0° IDC

8-pol., AWG23-22, 5,5 - 10mm, shielded, CAT6A

Push Pull RJ45 male - IDC terminal
IDC fast connection technology
Ethernet CAT6A
shielded

Link to Product

Illustration



Product may differ from Image



Side 1	
Family construction form	RJ45
Material contact	Bronze
No. of poles	8
Commercial data	
ECLASS-6.0	27279221

ECLASS-7.0	27440104
ECLASS-8.0	27440104
ECLASS-9.0	27440102
ECLASS-10.1	2744010
ECLASS-11.1	2744010
ECLASS-12.0	27440114
ETIM-5.0	EC002635
customs tariff number	85366990
GTIN	4065909027226
Packaging unit	1
Electrical data Supply	
Operating voltage AC (UL-listed)	56,5 V
Operating voltage DC (UL-listed)	56,5 V
Operating current max.	1,75 A
Industrial communication	
Supported protocol	Ethernet
Transfer parameters	CAT6A
Data transmission rate max.	10000 MBit/s
Installation Connection	
Connection	Cut clamps IDC
Tightening torque	2,5 Nm
Device protection	
Shielded	yes
Device protection Electrical	
Degree of protection (EN IEC 60529)	IP20
Pollution Degree	2
Insulation resistance min.	500 MΩ
Overvoltage category (EN 60950-1)	I
Mechanical data Material data	
Coating contact	nickel plated
Combustibility class (UL94)	V-0
Material gasket	NBR
Material contact carrier	PC
Locking material	Copper alloy
Mechanical data Mounting data	
Clamping range min.	6 mm
Clamping range max.	10 mm
Environmental characteristics Climatic	
Operating temperature min.	-40 °C
Operating temperature max.	70 °C
Conformity	
Product standard	IEC 61076-3-117 V.14
Connection type 1	
Family construction form	RJ45
Gender	female
No. of poles	8
PIN 1	TD +
PIN 2	TD -
PIN 3	RD +
PIN 4	n.c.

PIN 5	n.c.
PIN 6	RD -
PIN 7	n.c.
PIN 8	n.c.