


B10 Hood, low profile, IP65

Double locking lever, side entry M25

B10  
Hood (low)  
Double locking lever  
Cable outlet (right angle)  
IP65  
Technical data will be only guaranteed with Murrelektronik components.

Link to Product

Illustration



Product may differ from Image

Commercial data

|                       |               |
|-----------------------|---------------|
| ECLASS-6.0            | 27143424      |
| ECLASS-6.1            | 27261203      |
| ECLASS-7.0            | 27440202      |
| ECLASS-8.0            | 27440202      |
| ECLASS-9.0            | 27440202      |
| ECLASS-10.1           | 27440202      |
| ECLASS-11.1           | 27440202      |
| ECLASS-12.0           | 27440202      |
| ETIM-5.0              | EC000437      |
| customs tariff number | 85389099      |
| GTIN                  | 4048879646352 |
| Packaging unit        | 1             |

Installation

Cable outlet laterally

Installation | Connection

|                    |     |
|--------------------|-----|
| Mounting set       | M25 |
| Mating cycles min. | 500 |

Device protection | Electrical

|                                        |                                         |
|----------------------------------------|-----------------------------------------|
| Degree of protection (EN IEC 60529)    | IP65                                    |
| Additional condition protection degree | inserted, locked, with screw connection |

Mechanical data

Housing type Hood

| Mechanical data   Material data          |                      |
|------------------------------------------|----------------------|
| Coating housing                          | powder-coated        |
| Coating locking                          | verzinkt             |
| Material housing                         | Aluminum die casting |
| Locking material                         | Steel                |
| Mechanical data   Mounting data          |                      |
| Size                                     | B10                  |
| Height                                   | 51 mm                |
| Width                                    | 43 mm                |
| Depth                                    | 73 mm                |
| Locking techniques                       | Double locking lever |
| Environmental characteristics   Climatic |                      |
| Operating temperature min.               | -40 °C               |
| Operating temperature max.               | 100 °C               |
| Climatic category (EN IEC 60068-1)       | 40/100/21            |